

OCB SERIES - PRECISION ORIFICES WITH BARBS

Bodies are color coded and clearly marked with the size of the orifice (one end is a clear barb). Flow direction is also marked on the body and is always from the colored barb to the clear barb. Barbed connections allow for higher working pressures, compared to the plain orifices. These barbed orifices offer an *optional* filter (304 SS screen) to prevent clogging in unfiltered lines.

SPECIFICATIONS

ACCURACY:	Orifice Size +/- 0.0003"
MATERIALS:	FDA Approved Polycarbonate Buna-N (Nitrile) O-Rings
MAX. OPERATING PRESSURE:	100 PSI

ORDERING INFORMATION

ORIFICE SIZE	Body Color	BARB SIZE	FILTER SIZE (<i>Optional</i>)
003 = 0.003"	Gold	062 for 1/16" I.D. TUBING	F5 = 5 micron F40 = 40 micron F80 = 80 micron F100 = 100 micron
004 = 0.004"	Purple		
005 = 0.005"	White	125 for 1/8" I.D. TUBING	
007 = 0.007"	Yellow		
008 = 0.008"	Lt. Green		
009 = 0.009"	Lavender		
010 = 0.010"	Lt. Blue		
012 = 0.012"	Green		
014 = 0.014"	Orange		
016 = 0.016"	Grey		
017 = 0.017"	Brown		
019 = 0.019"	Red		
020 = 0.020"	Dk. Blue		
025 = 0.025"	Black		
030 = 0.030"	Beige		
035 = 0.035"	Dk. Grey		
040 = 0.040"	Teal		



DIMENSIONS

